# Ul Mego Series Plenum Fan

Models APM and APH

Greenheck's new AP series plenum fan is designed for today's air handler applications. Models APM and APH offer a value price point approach to your construction requirements. Both models utilize Greenheck's 12-blade aluminum airfoil wheel for low sound and high efficiency and are licensed to bear the AMCA Sound and Air Performance Seal.



**GREENHECK** 



Model APM

#### **Arrangement 4 Vertical**

APM sizes 15-24, APH sizes 15-40







Model APH

- Single pressure port on inlet cone allowing

with or without transducer (optional)

for easy field airflow measurements (standard)

- Sure-Aire™ flow measurment (piezometric ring)

**Airflow Measuring** 

### **Arrangement 3 Interchangeable Motor Position**

Arrangement 3 fans with motor position left or right can be field adjusted to allow changes during AHU construction.





#### **Improved Lead Time**

With the time between quote, order and delivery getting shorter, Greenheck is introducing new programs to speedup delivery of fans to keep your project on schedule. Fast Pass speeds up lead time to 15 days on common fan configurations with no price impact.

Quick Build can get your fan shipped fast. If time is critical your fan can ship in as little as 5 or 10 days.

Program	Lead Time
Standard	4 week
Fast Pass	15 Day (3 weeks)
Quick Build	5 Day, 10 Day

## AP Series Plenum Models APM & APH





#### **APM**

**APH** 

**Volume Range** 

**Static Pressure** 

**Sizes** 

Standard Construction

**Options** 

1,150 - 40,000 cfm

Up to 5 in. wg

15 - 40 - Arr 4 Horiz 15 - 24 - Arr 4 Vert 18 - 40 - Arr 3 MOF Horiz

Bolted Frame
Galvanized Finish
Set Screw Bearings
L<sub>10</sub> 40,000 Hours Bearing Life
Single Pressure Tap

Inlet Guards
Protective Cage
Belt Guards

Sure-Aire™ Isolators

Painted Construction Vibration Test 1,150 - 150,000 cfm

Up to 12 in. wg

15 - 60 - Arr 4 Horiz 15 - 40 - Arr 4 Vert

18 - 40 - Arr 3 MOF Horiz 18 - 66 - Arr 3 MOB Horiz

12 - 73 - Arr 1 MOB Horiz

Welded Frame
Painted Finish
Concentric Bearings
L<sub>10</sub> 80,000 Hours Bearing Life
Single Pressure Tap
Vibration Test

Inlet Guards
Protective Cage
Belt Guards

Sure-Aire™ Isolators

Extended Life Bearings Isolation Base

